

Manual Call Point FD7150



The manual call point FD7150 is designed for indoor installation as a component of an Addressable Fire Alarm System IFS7000 series. The unit is compatible with the requirements of the European Standard EN54-11:2001/A1:2005, EN54-17:2005/AC:2007.

The FD7150 manual call point has a built-in short circuit isolator for the signal loop. The communication between the addressable manual call point and the Panel is based on a private UniTalk protocol.

Technical data

Supply voltage:

– (10-30) VDC

Degree of protection:

– IP 40

Current in quiescent state:

– < 390 μ A

Current in alarm state:

– (3 \pm 1) mA

Electrical installation:

Through terminal for connecting wires with cross-section (0,5-1,5) mm²

Operational temperature range: -10°C to +55°C

Relative humidity resistance: (93 \pm 3)% at 40°C

Dimensions: 98 x 96 x 51 mm

Weight of the manual call point: 0.150 kg

The LED indicator provides the following status information:

– Duty mode:

the LED flashes shortly on 16s period

– Alarm condition:

the LED flashes with continuous light

– Activated short circuit isolator:

the LED flashes shortly on 1s period



Office building UniPOS,
1 Efr. Nikola Paskalev Str., Mladost 1, Sofia 1748, Bulgaria
Phone: +359 2 97 439 25, +359 2 97 444 69

47 San Stefano Str., Pleven 5800, Bulgaria
Phone: +359 64 891 100

www.unipos-bg.com